

# LOFEX<sup>®</sup>

## A4111 Industrial Polyester Film

### Product Description

LOFEX<sup>®</sup> A4111 is clear polyester film which is both-sides corona treated. It is designed to be used for release, laminex, tape with excellent mechanical properties and thermal stability. Also, it is possible to control film thickness according to customer needs.

### Application

Industrial Use (Release, Laminex, Tape, etc.)

### Typical Properties

	Properties	Unit	Value				Test Method
General	Thickness	μm	50	75	100	125	LOTTE CHEMICAL method
	Tensile Strength (MD/TD)	kgf/mm <sup>2</sup>	22 / 25	21 / 24	20 / 23	19 / 22	
Mechanical	Elongation (MD/TD)	%	170 / 110	170 / 110	170 / 110	170 / 120	ASTM D882
	F5 (MD/TD)	kgf/mm <sup>2</sup>	11.5 / 11.5	11.5 / 11.5	11.5 / 11.5	11.5 / 11.5	
Optical	Light Transmission	%	88	88	88	88	ASTM D1003
	Haze	%	2.0	2.5	3.4	4.5	
	Gloss(60°)	%	160	160	160	160	
Thermal	Heat Shrinkage 150 °C ×30Min (MD/TD)	%	1.0 / 0.1	1.0 / 0.1	1.0 / 0.1	1.0 / 0.1	LOTTE CHEMICAL method
Surface	Coefficient of Friction (μk)	-	0.3	0.3	0.3	0.3	ASTM D1894
	Surface Tension	Dyne/cm	52	52	52	52	ASTM D2578
Surface treatment			Both sides(Corona)				

\*This properties are typical values of products and do not guarantee for products.