

	<u>Physical Properties</u>	수정일자	2013. 06. 04
		LOTTE CHEMICAL RESEARCH INSTITUTE 115 Gajeong-book St. Yusung, Dajeon TEL) 042-879-1261,1262	

# PAPET HOT

# PET HOMOPOLYMER

## General Information

### Description

- PAPET HOT is Homo-PET Resin.
- Excellent optical clarity
- High stress crack resistance and toughness
- Good thermal stability

### Applications

- ◆ Hot fillable bottles (Juice, tea, sports drink)

## Physical Properties<sup>1</sup>

General Properties	Test Method	Nominal Values	
Intrinsic Viscosity	ASTM D4603	0.78	dl/g
Color L	ASTM D6290	85±4	-
Color b	ASTM D6290	-	-
Carboxyl End Group	LC METHOD	30.0 Max	eq/ton
Diethylene Glycol	LC METHOD	1.5 Max	wt%
Melting Point	ASTM D3418	253±3	°C
Chip Size	LC METHOD	1.5±0.2	g/100ea
		-	ea/g
Acetaldehyde	LC METHOD	1.0 Max	wtppm
H <sub>2</sub> O	LC METHOD	-	wtppm
Density	ASTM D1505	1.40±0.01	g/cm <sup>3</sup>

### Note

ISO 9001, 14001, /ITS 16949

<sup>1</sup> Physical Properties : these are not to be construed as specifications